

ALUMAGLO

ALUMINUM BRIGHTENER, ETCHANT AND CLEANER

Product Description

ALUMAGLO is a medium duty aluminium brightener that can be used to remove road film, rust, oxides, light oils and greases. Leaves a satin finish after cleaning. It is used by trucking companies, aluminium and plastic manufacturers, for exterior cleaning of aluminium trucks and trailers, and other types of aluminum.

Directions for Use

Apply ALUMAGLO with a low-pressure spray at a concentration from 25:1 to full strength depending on surface conditions and temperature. (Use higher concentrations at lower temperatures). Contact time is up to 10 minutes, depending on the end use concentration, soil conditions and temperature. For trucks & trailers, apply horizontally from the bottom up, and then rinse vertically from the top down to avoid streaking.

Pail & Brush: apply as above.

Immersion (plastic tanks only): Use at 10-20% dilution. Immerse for 5-20 minutes. Rinse well with water.

Physical Properties

Appearance:	Colorless liquid
Odour:	pungent
pH (100%):	< 1.0
Specific Gravity:	1.06

Features

Contains a blend of both Hydrofluoric acid and phosphoric acid
Has CFIA approval

Benefits

Effectively removes rust, oxides, lime and silicate soils
Effectively etches and brightens Aluminum
Can be used in food processing plants

Precautions

ALUMAGLO will etch glass and polished Aluminum, leaving a satin or hazy finish on both surfaces.
Please refer to Material Safety Data Sheet for disposal and handling procedures.

Disclaimer: The product information expressed above is only based on in house and practical field testing. Therefore, the parameters experienced in actual usage are beyond our control. Any recommendations are made without any warranty, either expressed or implied. Manufacturer's and Distributor's only obligation shall be to replace any defective product. Neither shall be liable for any loss, damage or injury, direct or consequential, arising from the use of this product.