



LIME REMOVER & DESCALER

- For alkaline-resistane soils and deposits
- Non-corrosive lime, calcium and rust remover and de-scaler
- Safe for use on variety of surfaces
- Low odor, leaves no residue

	ES57
APPEARANCE	Clear colorless to straw liquid
ODOR	OCA
SOLUBILITY	Soluble
RELATIVE DENSITY	~1.032
pH- VALUE	1.5 maximum
VISCOSITY	N/A
SHELF LIFE	3 year

SIZES	
ES57-6	946 mL (1 US quart)
ES57-4	3.78 L (1 US gallon)

END USE APPLICATIONS

Food Service: Delime/descale food processing equipment, coffee urns, espresso machines, kettles, dishmachines, steamtables, glassware and nursery bottles.

Washrooms: Shower stalls, urinals, toilet bowls, tubs and shower heads.

Hard Surfaces: Brick, stucco, steel, aluminum and porcelain surfaces.

Other: Animal cages, lab glassware, humidifiers, washing machines and drinking fountains.

BENEFITS

- Product is non-corrosive on skin, aluminum, stainless steel and mild steel
- No Fumes - Low odor
- Lengthens life of metals and porcelain
- No residue
- Not TDG nor DOT Regulated

CLEANING INSTRUCTIONS

Before using Lime Remover & Descaler, remove or protect all food products and packaging materials. After use, thoroughly rinse all surfaces with potable water.

TOILET BOWLS, URINALS & SINKS

Use full strength, wipe and rinse.

BRICK & STUCCO

Brush, wipe or roll on full strength. Let sit for 3-5 minutes then rinse off.

NOTE: Test on an inconspicuous area first.

GLASSWARE & NURSERY BOTTLES

Wash glassware in solution of 9 ounces of Lime Remover and Descaler to 3 gallons of unheated tap water. Soak or brush if necessary. Rinse thoroughly in clean water and drain dry.

STAINLESS STEEL FOOD PROCESSING EQUIPMENT

Apply full strength with hand or tank sprayer, saturated sponge or cloth. Rinse with clean water and wipe dry.

COFFEE URNS

Fill water jacket of urn with unheated tap water and add 3 ounces of Lime Remover and Descaler per gallon of water. Heat and let stand for 15 minutes. Drain and rinse thoroughly with water.

ANIMAL CAGES

For removal of urine scale and film, apply 50% solution of Lime Remover and Descaler and unheated tap water to the cages and trays or soak in a solution of 8 ounces. Lime Remover and Descaler per gallon of water. Rinse thoroughly and allow to drain dry.

DELIMING DISHMACHINES

Fill tank 2" to 3" below overflow level. Turn tank heaters on. Add 1 gallon of Lime Remover and Descaler and allow machine to run until lime scale disappears. Apply full strength to areas where spray does not reach. Where lime build-up is heavy, scrape excess deposits. Drain tank and refill with fresh water. Run machine for 5 minutes and drain. Delime as necessary to prevent heavy buildup.

DELIMING STEAM TABLES

Brush or spray Lime Remover and Descaler full strength on interior surfaces. Let stand 10 minutes, then fill with water. Turn on heat and bring to operating temperature and let stand for 10 minutes. Brush or scrape off remaining deposits. Drain and flush thoroughly with clean water.

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS.